

QuickScan® QS6500

Linear Imager

Data Sheet



Features:

- Aggressive linear imaging performance with up to 38 cm / 15" reading on 100% UPC labels
- Supports RSS and PDF-417 for future industry compatibility
- 2005 Sunrise compliant
- Multi-interface solution supports all popular host terminal interfaces
- Flash memory for easy software upgrades
- Built tough to withstand common POS abuse for many years
- Attractive, yet durable design to complement your point-of-sale

Mechanical

Dimensions

Height: 16.5cm / 6.0"
Width: 7.4cm / 2.9"
Length: 9.9cm / 3.9"

Weight: 181.4 g / 6.4 oz

Environmental

Temperature Rating

Operating: 0° to 50°C / 32° to 122° F
Storage: -40° to 70° C / -40° to 158° F

Humidity:

Operating: 5 to 95% NC
Storage/Transport: 5 to 95% NC

Vibration: Meets MIL STD-810E

Mechanical Shock: Withstands 50 drops from 15m / 5' to concrete

ESD Protection: Functional after multiple 25kv discharges.

Water & Dust: IEC529 Rating IP52DW

Electrical

Operating Voltage: +4.5 to 14VDC ±5%

Operating Current: 300mA @ 5VDC

Idle Current: 200mA @ 5VDC

Optical

Ambient Light Immunity

Artificial & Sunlight: 86,000 Lux

Light Source: 630nm Visible Red Diode

Scan Rate: 450 scans/sec max

Sensor: 2048 pixel linear imager

Scan Width: 16.5cm / 6.3" @ 17.8cm / 7" from nose

Resolution: 5 mils / .13mm

Print Contrast: 30% or greater

Pitch: ±60°

Skew: ±55°

Depth of Field: Refer to Chart below

| DEPTH OF FIELD Range Comparisons | | |
|-------------------------------------|---------------------------|----------------------------|
| LABEL DENSITY | RANGE* | |
| | 1D MODELS | PDF MODELS |
| 5 mil Linear | 51-127 cm / 2.0 - 50" | 5 - 11.4 cm / 2.0 - 4.5" |
| 7.5 mils | 2.5 - 17.8 cm / 1.0 - 70" | 2.5 - 16.2 cm / 1.0 - 6.0" |
| 10 mils | 0 - 30.5 cm / 0 - 12" | 0 - 26.7 cm / 0 - 10.5" |
| 13 mils / 100% UPC | 0 to 38 cm / 0 - 15" | 0 - 33 cm / 0 - 13" |
| 20 mils | Up to 61.0 cm / 24" | Up to 53.3 cm / 21" |
| 40 mils | Up to 101.6 cm / 40" | Up to 89 cm / 35" |

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Decoding Capability

1D Versions

- UPC A, E / EAN 8, 13 / JAN 8, 13
- Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- RSS-14, Expanded, Stacked, Limited
- ISBN / Bookland EAN
- Code 39 (with full ASCII)
- Pharmacode 39
- Code 128
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- IATA
- Code 16K
- Code 11
- Codabar/NW7
- UK/Plessey
- MSI/Plessey

PDF Models support these additional symbologies:

- RSS Composites
- PDF-417
- Micro-PDF

Communications

- RS-232
- Keyboard Wedge
- IBM 46XX
- IBM USB
- USB

Safety & Regulatory

Electrical: Complies to EN60950, CSA60950, UL60950

Emissions: Complies to: FCC-A; EN 55022-B; BSMI 13438; AS/NZS 3548; VCCI-B, ICES-003

Laser Classification: IEC 60825 Class 1 LED



PSC Inc.
959 Terry Street • Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140
PSC Barcode Limited (UK Office)
Axis 3, Rhodes Way, Watford
England WD24 4TR7
Tel: 44 0 1923 809500 • Fax: 44 0 1923 809505

www.psc.com



Copyright © PSC Inc. 2005. All rights reserved. • Protected to the fullest extent under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from PSC. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • PSC, the PSC logo, and QuickScan are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. • Product specifications are subject to change without notice.

